

Phone 216-361-0221  
Fax: 216-361-3111



NICOPRESS® LAP TYPE FENCE WIRE SLEEVES AND TOOLS				
NICOPRESS® SLEEVE SELECTION			NICOPRESS® TOOL SELECTION	
WIRE SIZE	SLEEVE STOCK NUMBER	APPROX. WEIGHT LBS./C	TOOL GROOVE	TOOLS
7 gauge	FW-5-6	4.7	FW-5-6	3-56
9 gauge	FW-4-5	2.3	FW-4-5	64-2345
10 gauge	FW-3-4	1.7	FW-3-4	64-2345
11 gauge	FW-3-4	1.7	FW-3-4	64-2345
12-1/2 gauge	FW-2-3	0.6	FW-2-3 FW-2-3 G	64-2345 32-234 51-G-887
12-1/2 gauge	FW-2-3 3/4"	1.2	FW-2-3 FW-2-3 G	64-2345 32-234 51-G-887
14-1/2 gauge	FW-1-2	0.3	FW-1-2	64-2345
15-1/2 gauge	FW-1-2	0.3	FW-1-2	64-2345
12-1/2 barbed	FW-4-5	2.3	FW-4-5	64-2345
13-1/2 barbed	FW-4-5	2.3	FW-4-5	64-2345
14 barbed	FW-3-4	1.7	FW-3-4	64-2345
15-1/2 barbed	FW-3-4	1.7	FW-3-4	64-2345

NICOPRESS® FENCE TAPS				
FENCE TAPS STOCK NUMBER	APPROX. WEIGHT LBS./C	NICOPRESS APPLICATION TOOL SELECTION		
		TOOL GROOVE	TOOLS	APPROX. SHIPPING WEIGHT (LBS.)
FWT-3-4	0.5	FW-3-4 FWT-3-4*	64-2345 32-234	7.0 2.5
FWT-4-5	0.65	FW-4-5	64-2345	7.0

\*32-234 for 12-1/2 Ga. Wire ONLY, FWT-3-4 tool die groove, 2 overlapped presses per tap.

NICOPRESS® SPLIT SPLICING SLEEVES				
STOCK NUMBER	APPROX. WEIGHT LBS./C	NICOPRESS APPLICATION TOOL SELECTION		
		TOOL NUMBERS	TOOLS DIE GROOVE	APPROX. SHIPPING WEIGHT (LBS.)
FS-2-3	0.6	64-2345	FW-2-3	7.0
FS-3-4	1.0	64-2345	FW-3-4	7.0

HAND TOOL SPECIFICATIONS			
MODEL NO.	WT. (LBS)	MODEL NO.	WT. (LBS)
64-2345	7.0	32-234	2.5
51-G-887	5.0	31-DC	2.5
51-MJ	5.0	31-DJ	2.5
3-56	13.0	31-CJ	2.5
FT-2345	7.0		

# NICOPRESS®

NICOPRESS® BUTT TYPE FENCE WIRE SLEEVES AND TOOLS				
NICOPRESS® SLEEVE SELECTION			NICOPRESS® TOOL SELECTION	
WIRE SIZE	SLEEVE STOCK NUMBER	APPROX. WEIGHT LBS./C	TOOL GROOVE	TOOLS
7 gauge	2-3/081-M	10.7	FW-3-4 M	64-2345 51-MJ
9 gauge	2-148-J	4.0	J	31-CJ or 31-DJ
10 gauge	2-134-J	3.8	J	31-CJ or 31-DJ
11 gauge	2-120-J	3.8	J	31-CJ or 31-DJ
12-1/2 gauge	5-109-D135	2.2	D	31-DJ or 31-DC
14-1/2 gauge	5-083-C	1.1	C	31-DC or 31-CJ
12-1/2 barbed	125-JFW	4.1	J	31-DJ or 31-CJ
13-1/2 barbed	135-JFW	4.5	J	31-DJ or 31-CJ
14 barbed	140-JFW	3.7	J	31-DJ or 31-CJ


**NICOPRESS MODEL FT-2345 ("FIVE IN ONE" TOOL)**

Extreme versatility provided in a "5 in 1" tool operation:

- 1) Splices wire
- 2) Cuts wire
- 3) Tensions wire
- 4) Removes staples
- 5) Removes wire sag



**Model FT-2345.** Can be used for any sleeve that requires Model 64-2345 tool.

BATTERY-POWERED TOOL AND DIES				
<b>Nicopress Model 5506</b> In-line battery-powered tool, with one-hand operation. Comes complete with carrying case, two lithium ion battery cartridges, and one battery charger. Weighs 7 lbs. with battery. Shipping weight approx. 19 lbs.	DIES FOR MODEL 5506			
	SLEEVE NO.	DIE NO.	SLEEVE NO.	DIE NO.
	FW-5-6	6-FW56	FS-2-3	6-FW23
	FW-4-5 FWT-4-5	6-FW45	125-JFW 135-JFW 140-JFW	6-J
	FW-3-4 FWT-3-4	6-FW34	2-148-J 2-134-J 2-120-J	6-J
	FW-2-3	6-FW23 6-OVAL-G	2-3/081-M	6-M 6-FW34
	FW-2-3 3/4"	6-FW23 6-OVAL-G	4-062-C 5-083-C	6-C
	FW-1-2	6-FW12	5-109-D135	6-D