

Nicopress® Storm Connector Quick Reference

Splicing Sleeves for Solid Aluminum Conductor- Full Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS./M)	STANDARD PACKAGE
AL 6 SOL-J	6	J	2½"	12.5	100
AL 4 SOL-X	4	X	2¾"	41	50
AL 2 SOL-X	2	X	3¼"	44	50

Splicing Sleeves for Stranded Aluminum Conductor – Full Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS./M)	STANDARD PACKAGE
AL 6 STR-J	6 (7 WIRE)	J	2½"	14	100
AL 4 STR-P	4 (7 WIRE)	P	2¾"	32.5	100
AL 2 STR-X	2 (7, 19 WIRE)	X	3¼"	54	50
AL 1 STR-G33	1 (7, 19 WIRE)	G33	6"	185	25
AL 266.8-75A	250 (7, 19, 37, 61 WIRE)	75A	14"	731	10
AL 336.4-76A	366.4 (19 WIRE)	76A	15"	1144	10

Splicing Sleeves for ACSR Conductor- Partial Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS./M)	STANDARD PACKAGE
1706-P	6 (6/1 WIRE)	P	3¼"	40	50
1704-P	4 (6/1, 7/1 WIRE)	P	3¼"	36	50
1702-X	2 (6/1 WIRE)	X	3¼"	54	50

Splicing Sleeves for Solid Copper Conductor – Full Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS./M)	STANDARD PACKAGE
1-128-J	8	J	2"	39	100
1-162-J	6	J	2¼"	35	100
1-204-P	4	P	2¾"	82	100
1-258-X	2	X	3"	146	50

Splicing Sleeves for Stranded Copper Conductor – Full Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS./M)	STANDARD PACKAGE
1-204-P	6 (3 WIRE)	P	2¾"	82	100
1-204/7-P	4 (7 WIRE)	P	2¾"	83	100
1-258-X	4 (3 WIRE)	X	3"	146	50
1-258/7-X	2 (7 WIRE)	X	3"	126	50
1-258/3-X	2 (3 WIRE)	X	3¾"	152	50
1-258/3-X	1 (7,19 WIRE)	X	3¾"	152	50

Nicopress® Storm Connector Quick Reference

Splicing Sleeves for Copper Covered Steel (Copperweld) Copper Composite Conductor – Full Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS./M)	STANDARD PACKAGE
1-8A-P	8A	P	5"	178	50
1-6A-P	6A	P	5½"	173	50
1-6A-P	6C	P	5½"	173	50

Splicing Sleeves for ACSR, AAAC (6201-T81), and 5005 Stranded Conductor – Full Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS./M)	STANDARD PACKAGE
661-P	6	P	9"	104	25
467-ORANGE	4	ORANGE	14"	272	25
1061-PLUM	1/0	PLUM	16½"	433	25

Reducing Sleeves for Stranded Copper to Stranded Copper Conductor						
STOCK NUMBER	CONDUCTOR SIZE (AWG) FROM	CONDUCTOR SIZE (AWG) TO	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS./M)	STANDARD PACKAGE
1-258/3-X	2 (3 wire)	1 (7 wire)	X	3¾"	152	50

Split Repair Sleeves for Copper Covered Steel (Copperweld) Copper Composite Conductor – Full Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS./M)	STANDARD PACKAGE
R1-8A-P	8A	P	4"	135	25
R1-6A-P	7A	P	4"	120	25
R1-6A-P	6A	P	4"	120	25
R1-6A-P	6C	P	4"	120	25
R1-6A-P	8D	P	4"	120	25

Split Repair Sleeves for ACSR, AAAC (6201-T81), and 5005 Conductor – Full Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS./M)	STANDARD PACKAGE
AR-4-3-ORANGE	4	ORANGE	12"	200	25
AR-4-3-ORANGE	3	ORANGE	12"	200	25

The National Telephone Supply Company | 5100 Superior Avenue, Cleveland OH 44103
 Toll Free 1-877-868-6080 | Phone: (216) 361-0221 | Fax: (216) 361-3111 | email: sales@nicopress.com