

Nicopress Storm Connector Quick Reference

Splicing Sleeves for Copper Covered Steel (Copperweld) Copper Composite Conductor – Full Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS/M)	STANDARD PACKAGE
1-8A-P	8A	P	5"	178	50
1-6A-P	6A	P	5½"	173	50
1-6A-P	6C	P	5½"	173	50

Splicing Sleeves for ACSR, AAAC (6201-T81), and 5005 Stranded Conductor – Full Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS/M)	STANDARD PACKAGE
661-P	6	P	9"	104	25
467-ORANGE	4	ORANGE	14"	272	25
1061-PLUM	1/0	PLUM	16½"	433	25

Reducing Sleeves for Stranded Copper to Stranded Copper Conductor					
STOCK NUMBER	CONDUCTOR SIZE (AWG) FROM TO	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS/M)	STANDARD PACKAGE
1-258/3-X	2 (3 wire) 1 (7 wire)	X	3¾"	152	50

Split Repair Sleeves for Copper Covered Steel (Copperweld) Copper Composite Conductor – Full Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS/M)	STANDARD PACKAGE
R1-8A-P	8A	P	4"	135	25
R1-6A-P	7A	P	4"	120	25
R1-6A-P	6A	P	4"	120	25
R1-6A-P	6C	P	4"	120	25
R1-6A-P	8D	P	4"	120	25

Split Repair Sleeves for ACSR, AAAC (6201-T81), and 5005 Conductor – Full Tension					
STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS/M)	STANDARD PACKAGE
AR-4-3-ORANGE	4	ORANGE	12"	200	25
AR-4-3-ORANGE	3	ORANGE	12"	200	25

Nicopress Storm Connector Quick Reference

Splicing Sleeves for Copper Covered Steel (Copperweld) Copper Composite Conductor – Full Tension

STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS/M)	STANDARD PACKAGE
1-8A-P	8A	P	5"	178	50
1-6A-P	6A	P	5½"	173	50
1-6A-P	6C	P	5½"	173	50

Splicing Sleeves for ACSR, AAAC (6201-T81), and 5005 Stranded Conductor – Full Tension

STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS/M)	STANDARD PACKAGE
661-P	6	P	9"	104	25
467-ORANGE	4	ORANGE	14"	272	25
1061-PLUM	1/0	PLUM	16½"	433	25

Reducing Sleeves for Stranded Copper to Stranded Copper Conductor

STOCK NUMBER	CONDUCTOR SIZE (AWG) FROM TO	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS/M)	STANDARD PACKAGE
1-258/3-X	2 (3 wire) 1 (7 wire)	X	3¾"	152	50

Split Repair Sleeves for Copper Covered Steel (Copperweld) Copper Composite Conductor – Full Tension

STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS/M)	STANDARD PACKAGE
R1-8A-P	8A	P	4"	135	25
R1-6A-P	7A	P	4"	120	25
R1-6A-P	6A	P	4"	120	25
R1-6A-P	6C	P	4"	120	25
R1-6A-P	8D	P	4"	120	25

Split Repair Sleeves for ACSR, AAAC (6201-T81), and 5005 Conductor – Full Tension

STOCK NUMBER	CONDUCTOR SIZE (AWG)	TOOL GROOVE	LENGTH	APPROX WEIGHT (LBS/M)	STANDARD PACKAGE
AR-4-3-ORANGE	4	ORANGE	12"	200	25
AR-4-3-ORANGE	3	ORANGE	12"	200	25