

**NICOPRESS COPPER & ZINC PLATED COPPER OVAL SLEEVES
 FOR STEEL AIRCRAFT CONTROL CABLE & WIRE ROPE**

NICOPRESS OVAL SLEEVES				NICOPRESS APPLICATION TOOL SELECTION						
Cable Size	Plain Copper Stock Number	Zinc Plated Copper Stock Number	Approx. Wt. (Lbs.) Per M	HAND TOOLS		BENCH TOOL HEAD		HYDRAULIC TOOL DIES		AT-PNEUMATIC
				Single-Groove Tool Stock No.	Multi-Groove Tool Stock No.	Single-Groove Stock No. (Heads Only)	Multi-Groove Stock No. (Heads Only)	3512 Die Stock Number	635 Die Stock Number	Power Head Stock Number
1/32"	17-1-B	27-1-B	0.6	31-B	17-BA 17-B4B					AT-B
3/64"	18-11-B4	28-11-B4	2	51-B4-887	17-B4B 33V-CGB4	51-B4-887 HEAD		12-OVAL-B4	OVAL B4	AT-B4
1/16"	18-1-C	28-1-C	3	51-C-887	33V-CGB4 32-VC-VG 64-CGMP•	51-C-887 HEAD 3-C-887 HEAD	64-CGMP HEAD 3V-CGMP HEAD	12-OVAL-C	OVAL C	AT-C AT-CGMP
3/32"	18-2-G	28-2-G	5	51-G-887	33V-CGB4 32-VC-VG 64-CGMP•	51-G-887 HEAD 3-G-887 HEAD	64-CGMP HEAD 3V-CGMP HEAD	12-OVAL-G	OVAL G	AT-G AT-CGMP
1/8"	18-3-M	28-3-M	17	51-M-850	64-CGMP• 63V-XPM• 51-MJ 3V-F6:X:M	51-M-850 HEAD 3-M-850 HEAD	64-CGMP HEAD 63V-XPM HEAD 51-MJ HEAD 3V-CGMP HEAD 3V-F6:X:M HEAD 3-MJ HEAD	12-OVAL-M	OVAL M	AT-M AT-CGMP AT-XPM AT-MJ
5/32"	18-4-P	28-4-P	23	51-P-850	64-CGMP• 63V-XPM•	51-P-850 HEAD 3-P-850 HEAD	64-CGMP HEAD 63V-XPM HEAD 3V-CGMP HEAD	12-OVAL-P	OVAL P	AT-P AT-CGMP AT-XPM
3/16"	18-6-X	28-6-X	49	51-X-850	63V-XPM• 3V-F6:X:M	51-X-850 HEAD 3-X-850 HEAD	63V-XPM HEAD 3V-F6:X:M HEAD	12-OVAL-X	OVAL X	AT-X; AT-XPM AT-X-F6‡
7/32"	18-8-F2	28-8-F2	48	51-F2-850 3-F2-850		51-F2-850 HEAD 3-F2-850 HEAD		12-OVAL-F2	OVAL F2	AT-F2
1/4"	18-10-F6	28-10-F6	78	3-F6-950	3V-F6:X:M	3-F6-950 HEAD	3V-F6:X:M HEAD	12-OVAL-F6	OVAL F6	AT-F6‡ AT-X-F6‡
5/16"	18-13-G9	28-13-G9	114	3-G9-950		3-G9-950 HEAD		12-OVAL-G9	OVAL G9	AT-G9‡
3/8"	18-23-H5	28-23-H5	153	3-H5-950		3-H5-950 HEAD		12-OVAL-H5	OVAL H5	
7/16"	18-24-J8	28-24-J8	302					12-OVAL-J8	OVAL J8	
1/2"	18-25-K8	28-25-K8	410					12-OVAL-K8	OVAL K8	
9/16"	18-27-M1	28-27-M1	551						OVAL M1	
5/8"	18-28-N5	28-28-N5	802						OVAL N5	

* Model also available with Cable Cutter. Specify 64-CGMP/Cutter Tool or 63V-XPM/Cutter Tool.
 ‡Must be crimped using accessory booster kit.

NICOPRESS STAINLESS STEEL OVAL SLEEVES

NICOPRESS OVAL SLEEVES			NICOPRESS APPLICATION TOOL SELECTION							
Cable Size	Stainless Steel Stock Number	Approx. Wt. (Lbs.) Per M	HAND TOOLS		BENCH TOOL HEAD		HYDRAULIC TOOL DIES		AT-PNEUMATIC	
			Single-Groove Tool Stock No.	Multi-Groove Tool Stock No.	Single-Groove Stock No. (Heads Only)	Multi-Groove Stock No. (Heads Only)	3512 Die Stock Number	635 Die Stock Number	Power Head Stock Number	
1/32"	168-1-VB	0.5	31-B							
3/64"	168-1.5-VB4	1.5	51-B4-887	33V-CGB4	51-B4-887 HEAD			12-OVAL-B4	OVAL B4	AT-B4
1/16"	168-2-VB4	1.5	51-B4-887		51-B4-887 HEAD			12-OVAL-B4	OVAL B4	AT-B4
3/32"	168-3-VC	2.3	51-C-887 3-C-887		51-C-887 HEAD 3-C-887 HEAD			12-OVAL-C	OVAL C	AT-C
1/8"	168-4-VG	3.8	51-G-887 3-G-887		51-G-887 HEAD 3-G-887 HEAD			12-OVAL-G	OVAL G	AT-G
5/32"	168-5-VM	14	51-M-850 3-M-850		51-M-850 HEAD 3-M-850 HEAD			12-OVAL-M	OVAL M	AT-M
3/16"	168-6-VP	21	51-P-850		51-P-850 HEAD			12-OVAL-P	OVAL 168-6-VP	AT-P
7/32"	168-7-VX	31	3-X-950		3-X-950 HEAD			12-OVAL-X	OVAL X	AT-X‡
1/4"	168-8-VF2	44	3-F2-950		3-F2-950 HEAD			12-OVAL-F2	OVAL F2	AT-F2‡
5/16"	168-10-VF6	57	—		—			12-168-F6	OVAL 168-10-F6	—

‡Must be crimped using accessory booster kit.

“NICOPRESS” is a Registered Trademark in the United States and Foreign Countries.

**NICOPRESS TIN PLATED COPPER OVAL SLEEVES
FOR STAINLESS STEEL AIRCRAFT CONTROL CABLE & WIRE ROPE**

NICOPRESS OVAL			NICOPRESS APPLICATION TOOL SELECTION							
Cable Size	Tin Plated Copper Stock Number	Approx. Wt. (Lbs.) Per M	HAND TOOLS		BENCH TOOL HEAD		HYDRAULIC TOOL DIES		AT-PNEUMATIC	
			Single-Groove Tool Stock No.	Multi-Groove Tool Stock No.	Single-Groove Stock No. (Heads Only)	Multi-Groove Stock No. (Heads Only)	3512 Die Stock Number	635 Die Stock Number	Power Head Stock Number	
3/64"	428-1.5-VB4	2	17-B4B 51-B4-887	33V-CGB4	51-B4-887 HEAD			12-OVAL-B4	OVAL B4	AT-B4
1/16"	428-2-VC	3	51-C-887	33V-CGB4 32-VC-VG 64-CGMP*	51-C-887 HEAD 3-C-887 HEAD	64-CGMP HEAD 3V-CGMP HEAD		12-OVAL-C	OVAL C	AT-C AT-CGMP
3/32"	428-3-VG	6	51-G-887	33V-CGB4 32-VC-VG 64-CGMP*	51-G-887 HEAD 3-G-887 HEAD	64-CGMP HEAD 3V-CGMP HEAD		12-OVAL-G	OVAL G	AT-G AT-CGMP
1/8"	428-4-VM	17	51-M-850	64-CGMP* 63V-XPM* 51-MJ 3V-F6:X:M 3-MJ	51-M-850 HEAD 3-M-850 HEAD	64-CGMP HEAD 63V-XPM HEAD 51-MJ HEAD 3V-CGMP HEAD 3V-F6:X:M HEAD 3-MJ HEAD		12-OVAL-M	OVAL M	AT-M AT-CGMP AT-XPM AT-MJ
5/32"	428-5-VP	24	51-P-850	64-CGMP* 63V-XPM*	51-P-850 HEAD 3-P-850 HEAD	64-CGMP HEAD 63V-XPM HEAD 3V-CGMP HEAD		12-OVAL-P	OVAL P	AT-P AT-CGMP AT-XPM
3/16"	428-6-VX	50	51-X-850	63V-XPM* 3V-F6:X:M	51-X-850 HEAD 3-X-850 HEAD	63V-XPM HEAD 3V-F6:X:M HEAD		12-OVAL-X	OVAL X	AT-X; AT-XPM AT-X-F6†
7/32"	428-7-VF2	47	51-F2-850		51-F2-850 HEAD			12-OVAL-F2	OVAL F2	AT-F2
1/4"	428-8-VF6	75	3-F6-950	3V-F6:X:M	3-F6-950 HEAD	3V-F6:X:M HEAD		12-OVAL-F6	OVAL F6	AT-F6†; AT-X-F6†
5/16"	428-10-VG9	120	3-G9-950		3-G9-950 HEAD			12-OVAL-G9	OVAL G9	AT-G9†
3/8"	428-12-VH5	155	3-H5-950		3-H5-950 HEAD			12-OVAL-H5	OVAL H5	
7/16"	428-14-VJ8	310						12-OVAL-J8	OVAL J8	
1/2"	428-16-VK8	420						12-OVAL-K8	OVAL K8	
9/16"	428-18-VM1	565						OVAL M1		
5/8"	428-20-VN5	822						OVAL N5		

* Model also available with Cable Cutter. Specify 64-CGMP/Cutter Tool or 63V-XPM/Cutter Tool.
†Must be crimped using accessory booster kit.

**NICOPRESS COPPER STOP SLEEVES
FOR STEEL AIRCRAFT CONTROL CABLE & WIRE ROPE**

NICOPRESS STOP SLEEVES			NICOPRESS APPLICATION TOOL SELECTION							
Cable Size	Plain Copper Stock Number	Approx. Wt. (Lbs.) Per M	HAND TOOLS		BENCH TOOL HEAD		HYDRAULIC TOOL DIES		AT-PNEUMATIC	
			Single-Groove Tool Stock No.	Multi-Groove Tool Stock No.	Single-Groove Stock No. (Heads Only)	Multi-Groove Stock No. (Heads Only)	3512 Die Stock Number	635 Die Stock Number	Power Head Stock Number	
1/32"	871-32-B	.75	31-B	17-BA 17-B4B				871-B	AT-B	
3/64"	871-12-B4	1.5	51-B4-887	17-B4B 33V-CGB4	51-B4-887 HEAD			12-OVAL-B4	OVAL B4	AT-B4
1/16"	871-1-C	2	51-C-887	33V-CGB4 32-VC-VG 64-CGMP*	51-C-887 HEAD 3-C-887 HEAD	64-CGMP HEAD 3V-CGMP HEAD		12-OVAL-C	OVAL C	AT-C AT-CGMP
1/16"	871-1-Q†	2	51-Q-929		51-Q-929 HEAD 3-Q-929 HEAD			871-Q	AT-Q	
3/32"	871-17-J	8		51-MJ 3-MJ		51-MJ HEAD 3-MJ HEAD		12-J	871-J	AT-MJ
3/32"	871-3-Q†	2	51-Q-929		51-Q-929 HEAD 3-Q-929 HEAD			871-Q	AT-Q	
1/8"	871-18-J	8		51-MJ 3-MJ		51-MJ HEAD 3-MJ HEAD		12-J	871-J	AT-MJ
5/32"	871-19-M	13		51-MJ 3-MJ		51-MJ HEAD 3-MJ HEAD		12-1-M	871-1-M	AT-MJ
3/16"	871-20-M	12		51-MJ 3-MJ		51-MJ HEAD 3-MJ HEAD		12-1-M	871-1-M	AT-MJ
7/32"	871-22-M	20		51-MJ 3-MJ		51-MJ HEAD 3-MJ HEAD		12-1-M	871-2-M	AT-MJ
1/4"	871-23-F6	60	3-F6-950	3V-F6:X:M	3-F6-950 HEAD	3V-F6:X:M HEAD		12-OVAL-F6	OVAL F6	AT-F6†; AT-X-F6†
5/16"	871-26-F6	55	3-F6-950	3V-F6:X:M	3-F6-950 HEAD	3V-F6:X:M HEAD		12-OVAL-F6	OVAL F6	AT-F6†; AT-X-F6†
3/8"	871-27-F6	45	3-F6-950	3V-F6:X:M	3-F6-950 HEAD	3V-F6:X:M HEAD		12-OVAL-F6	OVAL F6	AT-F6†; AT-X-F6†

†Electro-Galvanized Steel Sleeves
* Model also available with Cable Cutter. Specify 64-CGMP/Cutter Tool or 63V-XPM/Cutter Tool.
†Must be crimped using accessory booster kit.

**NICOPRESS ALUMINUM OVAL SLEEVES
FOR STEEL AIRCRAFT CONTROL CABLE & WIRE ROPE**

NICOPRESS OVAL SLEEVES			NICOPRESS APPLICATION TOOL SELECTION						
Cable Size	Aluminum Stock Number	Approx. Wt. (Lbs.) Per M	HAND TOOLS		BENCH TOOL HEAD		HYDRAULIC TOOL DIES		AT-PNEUMATIC
			Single Groove Tool Stock No.	Multi-Groove Tool Stock No.	Single Groove Stock No. (Heads Only)	Multi-Groove Stock No. (Heads Only)	3512 Die Stock Number	635 Die Stock Number	Power Head Stock Number
3/64"	188-1.5-VB4	0.7	51-B4-887	17-B4B 33V-CGB4	51-B4-887 HEAD		12-OVAL-B4	188-B4	AT-B4
1/16"	188-2-VC	1	51-C-887	33V-CGB4 32-VC-VG 64-CGMP*	51-C-887 HEAD 3-C-887 HEAD	64-CGMP HEAD 3V-CGMP HEAD	12-OVAL-C	188-C	AT-C AT-CGMP
3/32"	188-3-VG	3	51-G-887	33V-CGB4 32-VC-VG 64-CGMP*	51-G-887 HEAD 3-G-887 HEAD	64-CGMP HEAD 3V-CGMP HEAD	12-188-VG	188-VG	AT-G AT-CGMP
1/8"	188-4-VM	6	51-M-850	64-CGMP* 63V-XPM* 51-MJ 3V-F6:X:M 3-MJ	51-M-850 HEAD 3-M-850 HEAD	64-CGMP HEAD 63V-XPM HEAD 51-MJ HEAD 3V-CGMP HEAD 3V-F6:X:M HEAD 3-MJ HEAD	12-188-VM	188-VM	AT-M AT-CGMP AT-XPM AT-MJ
5/32"	188-5-VP	9.5	51-P-850	64-CGMP* 63V-XPM*	51-P-850 HEAD 3-P-850 HEAD	64-CGMP HEAD 63V-XPM HEAD 3V-CGMP HEAD	12-188-VP	188-VP	AT-P AT-CGMP AT-XPM
3/16"	188-6-VX	16	51-X-850	63V-XPM* 3V-F6:X:M	51-X-850 HEAD 3-X-850 HEAD	63V-XPM HEAD 3V-F6:X:M HEAD	12-188-VX	188-VX	AT-X; AT-XPM AT-X-F6‡
1/4"	188-8-VF6	27	3-F6-950	3V-F6:X:M	3-F6-950 HEAD	3V-F6:X:M HEAD	12-188-VF6	188-VF6	AT-F6‡; AT-X-F6‡
5/16"	188-10-VG92	48	3-G9-950		3-G9-950 HEAD		12-VG92	VG-92	AT-G9‡
3/8"	188-12-VH5	65	3-H5-950		3-H5-950 HEAD		12-OVAL-H5	OVAL H5	
7/16"	188-14-VK8	115					12-OVAL-K8	OVAL K8	
1/2"	188-16-VM1	172					12-188-VM1	188-VM1	

* Model also available with Cable Cutter. Specify 64-CGMP/Cutter Tool or 63V-XPM/Cutter Tool
‡Must be crimped using accessory booster kit.

**NICOPRESS ALUMINUM STOP SLEEVES
FOR STEEL AIRCRAFT CONTROL CABLE & WIRE ROPE**

NICOPRESS STOP SLEEVES			NICOPRESS APPLICATION TOOL SELECTION						
Cable Size	Aluminum Stock Number	Approx. Wt. (Lbs.) Per M	HAND TOOLS		BENCH TOOL HEAD		HYDRAULIC TOOL DIES		AT-PNEUMATIC
			Single-Groove Tool Stock No.	Multi-Groove Tool Stock No.	Single Groove Stock No. (Heads Only)	Multi-Groove Stock No. (Heads Only)	3512 Die Stock Number	635 Die Stock Number	Power Head Stock Number
1/16"	878-2-VC	0.83	51-C-887	33V-CGB4 32-VC-VG 64-CGMP*	51-C-887 HEAD 3-C-887 HEAD	64-CGMP HEAD 3V-CGMP HEAD	12-OVAL-C	188-C	AT-C AT-CGMP
3/32"	878-3-J	3.0		51-MJ 3-MJ		51-MJ HEAD 3-MJ HEAD	12-J	878-J	AT-MJ
1/8"	878-4-J	3.0		51-MJ 3-MJ		51-MJ HEAD 3-MJ HEAD	12-J	878-J	AT-MJ
5/32"	878-5-M	4.8		51-MJ 3-MJ		51-MJ HEAD 3-MJ HEAD	12-M	878-M	AT-MJ
3/16"	878-6-M	4.3		51-MJ 3-MJ		51-MJ HEAD 3-MJ HEAD	12-M	878-M	AT-MJ
1/4"	878-8-VF6	21	3-F6-950	3V-F6:X:M	3-F6-950 HEAD	3V-F6:X:M HEAD	12-OVAL-F6	188-F6	AT-F6‡; AT-X-F6‡
5/16"	878-10-VF6	19	3-F6-950	3V-F6:X:M	3-F6-950 HEAD	3V-F6:X:M HEAD	12-OVAL-F6	878-VF6	AT-F6‡; AT-X-F6‡
3/8"	878-12-VF6	16	3-F6-950	3V-F6:X:M	3-F6-950 HEAD	3V-F6:X:M HEAD	12-OVAL-F6	878-VF6	AT-F6‡; AT-X-F6‡

* Model also available with Cable Cutter. Specify 64-CGMP/Cutter Tool or 63V-XPM/Cutter Tool
‡Must be crimped using accessory booster kit.

NICOPRESS ALUMINUM OVAL SLEEVES FOR SYNTHETIC & FIBER ROPE

NICOPRESS OVAL SLEEVES			NICOPRESS APPLICATION TOOL SELECTION						
Cable Size	Aluminum Stock Number	Approx. Wt. (Lbs.) Per M	HAND TOOLS		BENCH TOOL HEAD		HYDRAULIC TOOL DIES		AT-PNEUMATIC
			Single-Groove Tool Stock No.	Multi-Groove Tool Stock No.	Single-Groove Stock No. (Heads Only)	Multi-Groove Stock No. (Heads Only)	3512 Die Stock Number	635 Die Stock Number	Power Head Stock Number
1/16"	1700-C	1	51-C-887	64-CGMP	51-C-887 HEAD 3-C-887 HEAD	64-CGMP HEAD 3V-CGMP HEAD	12-OVAL-C	188-C	AT-C AT-CGMP
1/8"	1700-M	7	51-M-850 3-M-850	64-CGMP 63V-XPM	51-M-850 HEAD 3-M-850 HEAD	64-CGMP HEAD 63V-XPM HEAD 3V-CGMP HEAD	12-1700-M	1700-M	AT-M AT-CGMP AT-XPM
3/16"	1582-P	9	51-P-850 3-P-850	64-CGMP 63V-XPM	51-P-850 HEAD 3-P-850 HEAD	64-CGMP HEAD 63V-XPM HEAD 3V-CGMP HEAD		1582-P	AT-P AT-CGMP AT-XPM
1/4"	1700-X	20	51-X-850 3-X-850	63V-XPM	51-X-850 HEAD 3-X-850 HEAD	63V-XPM HEAD		1700-X	AT-X AT-XPM
5/16"	1700-G3	30					12-1700-G3	1700-G3	
3/8"	1700-H5	63					12-1700-H5	1700-H5	
1/2"	1700-J8	110					12-1700-J8	1700-J8	

NICOPRESS® TOOLS

	Approx. Shipping Weight (Lbs.)
TOOL & SLEEVE SPLICE KITS	
Kit No.1 #3293 (Zinc/Copper); 64-CGMP/Cutter Tool	21.0
Kit No.2 #3311 (Zinc/Copper); 63V-XPM/Cutter Tool	26.0
Kit No.3 #3601 (Copper)	2.6
Kit No.4 #3602 (Zinc / Copper)	2.6
Kit No.5 #3603 (Tin / Copper)	2.6
Kit No.6 #3604 (Aluminum)	1.3

HAND TOOLS

17-BA: Pliers-action tool	0.8
17-B4B: Pliers-action tool	0.8
31-B: Single-groove toggle-action tool	2.2
32-VC-VG: Multi-groove toggle-action tool	2.2
33V-CGB4: Multi-groove toggle-action tool	2.5
51 Series Single-groove, toggle-action & 51-MJ model	5.0
63V-XPM & 64-CGMP: Multi-groove toggle-action tool	6.5
3 Series: Single-groove toggle-action tool	13.0
3V Series: Multi-groove toggle-action tool	13.4

HAND TOOLS WITH CUTTER

64-CGMP & 63V-XPM Combination Cutter/ Multi-groove toggle-action tool	7.0
64-CGMP & 63V-XPM Head with Cutter (Replacement head for hand tool)	2.4

BENCH TOOLS AND HEADS

510 Bench Tool	6.0
51 Series Head: Single-groove tool head	1.8
63V & 64 Head: Multi-groove tool head	2.2
300 Bench Tool	19.0
3 Series Head: Single-groove tool head	4.4
3V Series Head: Multi-groove tool head	4.6

HYDRAULIC COMPRESSION TOOLS

MODEL 3512 HYDRAULIC TOOLS AND DIES

3512 WC: Hydraulic Hand Compression Tool with Molded Plastic Case. (Approx. wt. 21 lbs.)

No. 12 Compression Die for 3512 Tool (Wt. 0.5 lb.)

3512-H: Power Head only, with case. Includes 6-foot hose and fittings. (Approx. wt. 21 lbs.)

MODEL 635 HYDRAULIC TOOLS AND DIES

635: NICOPRESS Manual Hydraulic Compression Tool. Shipped complete with hand pump, mounted on a base, and packed in a metal carrying case. (Approx. wt. 73 lbs)

635-A: NICOPRESS hydraulic compression tool head. Shipped with quick-disconnect coupling, six foot hydraulic hose, and is ready for hook-up To power source. Includes metal carrying case. (Approx. wt. 45 lbs)

Die Set for Model 635 or 635-A Tool (Wt. 1.5 lbs)

2498 Cable Cutter Die for Model 635 or 635-A (Wt. 1.5 lbs)

Conversion Assemblies and Extension Hose Assemblies are available for: 1) converting the Model 635 tool with hand pump to power operation; and/or (2) extending hose lengths for operation of the Model 635-A or 3512-H.

HYDRAULIC POWER SOURCES FOR 635-A & 3512-H

AIR/HYDRAULIC POWER SOURCE

Model NAH-1: Air-driven hydraulic source, 80-110# air pressure. Output is 15 cu. in. per minute at 10,000 PSI. Approx. wt. 20 lbs.

ELECTRIC/HYDRAULIC POWER SOURCE

Model NEH-1: Electric motor driven hydraulic pump, 115 volt, 60 HZ-AC power. Hydraulic output is 20 cu. in. per minute at 9,200 PSI. Approx. wt. 33 lbs.

BATTERY-POWERED TOOLS

Model 5606: In-line battery-powered tool

Model 5512: Handle-grip battery-powered tool

Model 5612: Pistol-grip battery-powered tool

6-Series Die: Die for Model 5606 tool

12-Series Die: Die for Model 5512 or 5612 tool

NBP-1: Battery Cartridge replacement

NCH-1: Battery Charger replacement

Note: Tools come complete with carrying case, two battery cartridges, and one battery charger.

PNEUMATIC POWER CRIMP TOOLS

PNEUMATIC TOOLS AND ACCESSORIES

AT-330: Pneumatic Hand Crimp Tool.

Portable handled model operates on standard shop air pressure (85-95 PSI). Incl. shoulder strap, hex wrench, instructions. (Approx. wt. 13 lbs.)

ATB-330: Pneumatic Bench Tool with foot switch control. Operates on standard shop air pressure (85-95 PSI). Built in air filter, regulator. Includes adapter bracket, instructions. (Approx. wt. 28 lbs.)

AT-330FC: Optional foot control assembly. Converts handled tool to bench operation. Includes adapterbracket, instructions. (Approx. wt. 10 lbs.)

AT BOOSTER: Optional booster accessory extends crimp range to 5/16" cable. (Approx. wt. 6 lbs.)

CRIMP HEADS FOR PNEUMATIC TOOLS

Single-groove Heads: AT-B4, AT-C, AT-G, AT-M, AT-P, AT-X, AT-F2, AT-F6 and AT-MJ (Wt 4 lbs.)

Multi-grooved Heads: AT-CGMP, AT-XPM, AT-X-F6, and ATG9 (Wt. 5 lbs.)

IMPORTANT INFORMATION

For more than 70 years the NICOPRESS COMPRESSION SYSTEM has been used with wire rope, aircraft control cable, and fiber rope. NICOPRESS OVAL SLEEVES are used to eye-splice and NICOPRESS STOP SLEEVES are used to terminate cable and rope.

Detailed instruction sheets showing proper NICOPRESS TOOL operation and adjustment, plus gauges for checking sleeve compression are packaged with each tool.

We have determined through pull testing that **copper, plated copper** and **stainless steel** Nicopress Oval Sleeves will hold military specification grade aircraft control cable in tension until it breaks, when the cable is made to military specifications: MIL-DTL-83420M, dated 2-17-09 for cable constructions 3x7, 7x7 and 7x19, and RR -W-410F dated 12-6-07 for cable constructions 6x19 IWRC.

Other types and grades of cable exist and may be used with Nicopress Sleeves. In order to establish the exact holding power of a Nicopress Sleeve when used with other types of cable, we recommend pull testing prior to use. This step insures proper selection of materials, the correct pressing procedure, and an adequate margin of safety for the intended use.